



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: MP Sanded 924 Grout

Product Use: Sealant.

Manufacturer/Supplier: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA
90740

Phone Number: (562) 598-8808

Emergency Phone: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500

Date of Preparation: October 25, 2010 **Revision Date:** October 25, 2010

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

- Eye:** Irritating to eyes. May cause burns in the presence of moisture.
- Skin:** May cause skin irritation. May cause burns in the presence of moisture.
- Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
- Inhalation:** May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, dust may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Silica, crystalline, quartz	14808-60-7	40 - 70
Portland cement	65997-15-1	15 - 40
Titanium dioxide	13463-67-7	1 - 5
Kaolin	1332-58-7	1 - 5
Calcium formate	544-17-2	1 - 5
Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	9084-06-4	0.1 - 1
2,2-dimethylpropane-1,3-diol	126-30-7	0.1 - 1



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable by WHMIS/OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Treat for surrounding material.
 - Unsuitable Extinguishing Media:** Not available.
- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
 - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
- Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill with inert material, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Clean-Up:** Scoop up material and place in a disposal container.
- Other Information:** Not available.

Section 7: HANDLING AND STORAGE

- Handling:** Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

Storage:

Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Silica, crystalline, quartz	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)); ((30 mg/m ³)/(%SiO ₂ +2) TWA (total));	0.025 mg/m ³
Portland cement	((250)/(%SiO ₂ +5) mppcf TWA (resp))	10 mg/m ³ (total)
Titanium dioxide	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³
Kaolin	10 mg/m ³	2 mg/m ³
Calcium formate	15 mg/m ³	Not available.
Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	Not available.	Not available.
2,2-dimethylpropane-1,3-diol	Not available.	Not available.

Engineering Controls: When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.
Color:	White, grey or coloured.
Odour:	Not available.
Odour Threshold:	Not available.
Physical State:	Solid.
pH:	Not available.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

Flash Point:	Not available.
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	2.7
Solubility in Water:	Negligible.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, %:	0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Keep dry in storage.

Conditions of Reactivity: Heat. Incompatible materials. Moisture.

Incompatible Materials: Acids. Ammonium salts. Aluminum. Alkali and alkaline earth metals.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC₅₀
Silica, crystalline, quartz	500 mg/kg, rat	Not available.
Portland cement	Not available.	Not available.
Titanium dioxide	>10000 mg/kg, rat	Not available.
Kaolin	Not available.	Not available.
Calcium formate	2650 mg/kg, rat	Not available.
Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	3800 mg/kg, rat	Not available.
2,2-dimethylpropane-1,3-diol	3200mg/kg, rat	Not available.

Eye: Irritating to eyes. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: May cause skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Lungs.

Chronic Effects: Hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Hazardous by WHMIS/OSHA criteria.

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Silica, crystalline, quartz

G-A2, I-1, N-1, CP65

Portland cement

Not listed.

Titanium dioxide

G-A4, I-2B

Kaolin

Not listed.

Calcium formate

Not listed.

Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt

Not listed.

2,2-dimethylpropane-1,3-diol

Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

Not regulated

TDG Classification

Not regulated



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Titanium dioxide	Not listed.	Not listed.	Not listed.	Not listed.
Kaolin	Not listed.	Not listed.	Not listed.	Not listed.
Calcium formate	Not listed.	Not listed.	Not listed.	Not listed.
Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	Not listed.	Not listed.	Not listed.	Not listed.
2,2-dimethylpropane-1,3-diol	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product contains a chemical known to the state of California to cause cancer.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Silica, crystalline, quartz	DSL	Yes.
Portland cement	DSL	Yes.
Titanium dioxide	DSL	Yes.
Kaolin	DSL	Yes.
Calcium formate	DSL	Yes.
Naphthalenesulfonic acid, polymer with formaldehyde, sodium salt	DSL	Yes.
2,2-dimethylpropane-1,3-diol	DSL	Yes.

All ingredients are on DSL/NDSL and TSCA inventories or are exempt from listing.

HMIS - Hazardous Materials Identification System

Health - 2* Flammability - 0 Physical Hazard - 0 PPE - E

NFPA - National Fire Protection Association:

Health - 2 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Chronic Toxic Effects
- Class D2B - Skin/Eye Irritant



MATERIAL SAFETY DATA SHEET

MP Sanded 924 Grout

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

- OSHA (O)** Occupational Safety and Health Administration.
- ACGIH (G)** American Conference of Governmental Industrial Hygienists.
A1 - Confirmed human carcinogen.
A2 - Suspected human carcinogen.
A3 - Animal carcinogen.
A4 - Not classifiable as a human carcinogen.
A5 - Not suspected as a human carcinogen.
- IARC (I)** International Agency for Research on Cancer.
1 - The agent (mixture) is carcinogenic to humans.
2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
- NTP (N)** National Toxicology Program.
1 - Known to be carcinogens.
2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: October 25, 2013

Version #: 1.0

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com